


COEX™ C3000 Thermal IP Fixed Camera Station

The COEX™ C3000 Thermal IP Fixed Camera Station has a unique compact and lightweight design developed specifically for hazardous-area applications. C3000 camera stations are designed for both toughness and durability as demanded for operation in the most adverse of environments, while allowing constant visual feedback in zero-light conditions.



COEX C3000 hazardous-area camera stations operate in the most extreme environments worldwide. Designed for toughness, durability, and certified to perform in ambient temperatures from -55°C to +70°C without compromise, they are ideal for oil and gas, marine, and industrial installations.

This premium-performance camera station delivers superb thermal imaging in all lighting conditions and across long distances.

Featuring the latest encoding technology (3rd generation IP encoder), the camera station is capable of triple-stream H.264 and H.265 encoding for simultaneous live view and recording.

Utilizing the advanced radiometry feature, the camera station can provide real-time temperature data and differential temperature monitoring of critical devices and applications.

The C3000 Thermal IP Fixed Camera Station has cybersecurity measures built-in, including encrypted video streaming, HTTPS, and 802.1x protocols.

This camera station is compatible with a variety of VMS platforms through ONVIF Profile S and T compliance.

Options

- Advanced radiometry

 ATEX	 IEC/IECEX	 ONVIF S T
 IP66/IP68	 316L STAINLESS STEEL	 H.264 H.265
 CYBERSECURITY	 -55°C/+70°C	 THERMAL SENSOR
 Triple Streaming	 Direct Ethernet	 RADIOMETRICS

Specifications

CERTIFICATIONS / RATINGS ^{*4}		[OPTIONS]
ATEX / IECEx / UKCA	ATEX II 2GD, Ex db IIB/IIC Gb; Ex tb IIIC Db; T4 / T5 / T6 EN60079-0, EN60079-1, EN60079-31, IEC60079-0, IEC60079-1, IEC60079-31	
ATEX / IECEx / UKCA Certified Temperature	-55°C to +50°C (T6), +60°C (T5), +70°C (T4)	
CE / UKCA	IEC62368-1, IEC60825-1	
DNV	Pending	
INMETRO	BRA 21.GE0018X	

ENVIRONMENTAL	
Operating Temperature	-45°C to +70°C / -49°F to +158°F
Storage Temperature	-45°C to +80°C / -49°F to +176°F
Ingress Protection	IP66 & IP68 (30m Submersion for 4 hrs) to IEC60529 Type 6 Enclosure
Salt Mist	IEC60068-2-52 & IEC60945 Section 8.12
Vibration	0.7 g to IEC60068-2-6 & IEC60945
Wind Loading	Operational to 130 km/h, survival to 268 km/h
Humidity	5% to 95%

MECHANICAL	
Material	Electro-polished 316L stainless steel
Window	Germanium window with DLC (Diamond-Like Carbon) coating and impact guard
Mounting Orientation	Upright or inverted
Mounting Base	1 x Ø12.5 mm / 0.49" fixing hole
Dimensions ^{*1} (W x D x H)	179 x 310 x 235 mm / 7.05" x 12.21" x 9.25"
Weight ^{*1}	8 kg / 17.6 lb
Cable Gland Entries	1 x M20

ELECTRICAL	
Input Power Options	24 V AC/DC (±10%) 50/60 Hz
Power Consumption ^{*1}	8 VA Quiescent 12 VA Max
Auxiliary Inputs ^{*2}	1 x contact closure input (5 V pull up) [up to 4 available on request]
Relay Outputs ^{*2}	1 x volt free switched output (24 V 0.75 A max) [up to 2 available on request]
Audio ^{*2}	[Line Input]

CAMERA OPERATION	
Preset Memory	128 user programmable preset positions (digital zoom)
ONVIF Control Features	Digital zoom control, preset store/recall, alarm inputs, and relay outputs

THERMAL IMAGER	T306	T318	T618	T636
Image Sensor	Uncooled LWIR VOx microbolometer			
Pixel Pitch	12 µm			
Thermal Sensitivity	<50 mK at f/1.0			
Spectral Response	8- 14 µm			
Refresh Rate	7>9Hz [>60Hz] [25 Hz / 30 Hz]			
Pixel Resolution	320 x 256		640 x 512	
Fixed Focal Length	6.3 mm f/1.0	18 mm f/1.0	18 mm f/1.0	36 mm f/1.0
Angle of View	34.1° x 27.3°	12.7° x 9.7°	24.3° x 19.5°	12.2° x 9.8°
Features	8x digital zoom, auto/manual gain mode (AGC), auto/manual FFC(NUC), selectable color palettes, second generation digital detail enhancement (DDE), image optimization, active contrast enhancement (ACE), information based histogram equalization (IBHEQ)			
Advanced Radiometry	When used with Synergy, the advanced radiometry feature provides four regions of interest per preset position that can be individually monitored or compared against one another for temperature threshold changes.			

VIDEO ENCODING

Compression Standards	H.264 (MPEG4 part 10/AVC) high, main, base profiles H.265 (MPEG-H part 2/HEVC), MJPEG
Bitrate Mode	Constant Bitrate (CBR), Variable Bitrate (VBR)
Encoding Capability	Up to 3 independently configurable encoded video streams
Stream Bitrate* ³	100 kb/s to 25 Mb/s
Image Resolution* ³	Native (640x512 or 320x256), D1 (720 x 576/480), VGA (640 x 480), QVGA (320 x 240)
Image Rate* ³	Full, half, quarter, sixth
GOP Structure	I-frame only, 5 to 240 frames
Region of Interest (ROI)	Configurable per encoded video stream, ability to crop a selected area of the image source for encoding (variable resolution and aspect ratio)

AUDIO ENCODING

Compression Standards	ARM AACLC, ARM AACLC MPEG2, ARM AACHE, ARM AACHE V2
Sample Rate	48 kHz, 44.1 kHz, 32 kHz, 16 kHz
Stream Bitrate	12 to 384 kb/s (AACHE and AACHE V2 32 to 64 kb/s)

NETWORK DEVICE

Interface Options	Ethernet (100Base-T, 10-Base-T), Auto/full/half duplex, Auto/10/100, Configurable MTU Size
Protocols	TCP/IP, UDP, ICMP, DHCP, DNS, HTTP, HTTPS, NTP, RTSP/RTP/RTCP, TSRTSP, RTMP, RTMPS, SRT, IGMP, SNMP, SYNS, SSL, TLS, 802.1x (EAP)
Control Protocol	SYNS, ONVIF (Profile S, T compliant)
Video Stream Delivery	RTSP/RTP (Unicast: UDP/TCP, Multicast UDP), TSRTSP, RTMP, RTMPS, SRT
Network Discovery	SYNS, WS-Discovery (ONVIF)
Device Security	Multiple users and 7 access levels protecting access to the web interface, ONVIF and RTSP services, HTTPS support, HTTP disable, 802.1x (EAP), video streaming disabled until change of default password, unicast stream disable
Supported Internet Browsers	Chrome/Firefox/IE/Edge (No Active-X browser components required)
System Maintenance	Field upgradeable firmware, diagnostic logs Hardware system supervisor providing temperature management, cold-start, auto-shutdown and watchdog control

NOTE: *1 Dependent on certification and equipment fitted. *2 Dependent on cable tail option. *3 Maximum permissible resolution, bitrate and framerate per additional stream will be reduced dependent on the configuration of the primary stream. *4 Exact certification requirements must be specified at the time of order.

PART CODE STRUCTURE

C3 - A B C D - E - F G H J

(Example) C3 - 1 F T306 - B 5 E X

A - CAMERA HOUSING SIZE

1 Size 1 camera housing

B - FIXED/PTZ

F Fixed

C - DAY/NIGHT CAMERA

N/A

D - THERMAL IMAGING MODULE

T306 Medium resolution, 35° HFOV
 T318 Medium resolution, 13° HFOV
 T618 High resolution, 25° HFOV
 T636 High resolution, 12° HFOV

E - WIPER

N/A

J - SPECIAL

Standard build

X Special build

H - OUTPUT TRANSMISSION TYPE

E Ethernet Base-T

G - BASE/MOUNTING TYPE

Standard fixed mounting

5 Alternative fixed mounting

F - TECHNOLOGY SERIES

B 3rd Gen, IP encoder